# **LUMEN KING LED**


# **GROW LIGHT 630W**



#### TECHNICAL SPECIFICATIONS

Light Source	LED
Spectrum	Full Spectrum
PPF	1650 μmol/s
Input Power	630W
Efficacy	2.6 μmol/J
Input Voltage	120-277V
Mounting Height	≥ 6" Above Canopy
Thermal Management	Passive
Dimming	0-10V Signal Knob
Beam Angle	120°
Power Factor	>90 %
Certifications	ETL/DLC/(UL Optional)
Diodes Brand	Samsung + Osram/Cree
Drivers Brand	Sosen/MeanWell
Waterproof rating	IP65
Operation Temperature	-20° - 45°C
Operation Humidity	10%-95% RH
Storage Temperature	-20° - 80°C
Storage Humidity	10%-95% RH
Warrantly Time	5 years

#### SPECTRUM




# ITEMS INCLUDED IN THE BOX

6 x LUMEN KING 105 W 2.6 Full-Spectrum Magnet Light Bars


- 1 x Foldable Frame Structure with 2 x 315 W Incorporated Drivers + Connecting cables
- $2\,x$  Metal Plates Fixed in structure to ensure fixture balances
- 1 x 0-10V Light Dimmer + RJ Inputs
- 2 x Metal Fixture Wire Hangers
- 1 x User Manual

DIMENSIONS					
Part	LENGTH	WIDTH	HEIGHT	WEIGHT	
LUMEN KING	40,15"	39,37"	3,14"	26,45 lbs	
Light fixture	1020mm	1000mm	80mm	12 Kg	
LUMEN KING	43,30″	23,62"	7,87"	39,68 lbs	
Package Size	1100mm	600mm	200mm	18Kg	

#### PRODUCT DIMENSIONS



### PPFD TESTING REPORT



# INFORMATION

PPF calculations complied using our in-house integrating sphere measurements and typical spectroadiometric data for each LED fixture performance.

Watts Value are typical expected values. Tolerance allow +/- 10% range on flux and power consumption.



Contact LUMENKING (a) info@lumen-king.com (a) www.lumen-king.com/led-grow-lights (a)